RICH SOLAR | ALPHA™ Series Batteries

ALPHA 3 PRO
LiFePO$_4$ BATTERIES 12.8V 314Ah



Safety & Structural Reliability

Grade A+ LiFePO$_4$ cells ensure long-term stability and thermal safety.

Advanced BMS provides comprehensive multi-level electrical and thermal protection.

UL94 V-0 flame-retardant housing and IP65 waterproof construction enhance durability.

All-Weather Operation & Cold Protection

Wide operating range: Charge 32–131°F | Discharge −4–140°F.

Built-in low-temperature charging protection with automatic recovery supports safe winter operation.

Internal Heating Technology activates below 41°F and stops above 50°F to support safe charging in freezing climates.

Long Lifespan & Energy Efficiency

Industry-leading cycle life: ALPHA 3 PRO 8,000+ cycles.

Provides 4,019Wh of energy capacity with up to 200A continuous discharge.

Maintenance-free LiFePO$_4$ chemistry provides clean, stable, and efficient power output.

Smart Integration & Expandability

Bluetooth Monitoring: Track SOC, voltage, current, temperature, cycle count, and system status via the RICH SOLAR App.

Supports up to 4 units in parallel (4P) for RVs, marine, off-grid cabins, and backup power systems.

Backed by a 10-year Warranty.

Intertek FC CE UN38.3 MSDS

© 2026 RICH SOLAR ALL RIGHTS RESERVED

SPECIFICATIONS

BATTERY

Model	RS-B123SP
Product Name	ALPHA 3 PRO
Nominal Voltage	12.8V
Rated Capacity	314Ah
Nominal Energy	4,019Wh
Cell Chemistry	$LiFePO_4$
Cycle Life (80% DoD)	8,000+
Parallel Expansion	Up to 4 units (4P)
Bluetooth	Yes
Internal Heating	Yes (100W)
Certifications	ETL, FCC, CE, UN 38.3 & MSDS

ELECTRICAL PERFORMANCE & CHARGING

Charging Method	CC/CV
Max Charge Voltage	14.4V
Recommended Charge Voltage	14.2V
Discharging Cutoff Voltage	10.0V
Recommended Charge Current	157A
Max Charge Current	200A
Max Continuous Discharge Current	200A

ENVIRONMENTAL

Charge Temperature	32°F to 131°F
Discharge Temperature	-4°F to 140°F
Storage Temperature	-22°F to 131°F (<1 Month) / 14°F to 113°F (>3 Months), ≤90% RH
Low-Temperature Charging Protection Auto Recovery	Yes
Ingress Protection	IP65

MECHANICAL

Terminals	M8
Housing Material	UL94 V-0 flame-retardant plastic
Dimensions (L × W × H)	20.5 × 10.6 × 8.7 in
Net Weight	71.7 lbs

BMS CAPABILITIES (COMMON ACROSS ALL MODELS)

Voltage Protection	Over-Charge Protection	Yes
	Over-Discharge Protection	Yes
Current Protection	Charging Over-Current Protection	Yes
	Discharging Over-Current Protection	Yes
Circuit Protection	Short-Circuit Protection	Yes
Temperature Protection	High/Low Temperature Charging Protection	Yes
	High/Low Temperature Discharging Protection	Yes
	Internal FET Over-Temperature Protection	Yes
Cell Management	Passive Cell Balancing	Yes

SPECIFICATIONS INCLUDED IN THIS DATASHEET ARE SUBJECT TO CHANGE WITHOUT NOTICE.